



**MATERIALS & FEATURES**

- Steel ASTM A36 sheet metal
- Laser cut steel bent and welded forms the base plate
- Lock bar made from 3/4" A36 solid steel rod controls bikes and prevents rubbing
- Polyvinyl sleeve on hook to prevent metal-to-metal contact when parking and removing bike
- Tire hook has a large profile to accommodate fat tire bikes (up to 4.8" rims), and has a dimpled center to locate smaller mountain bike and road bike tires.

**FINISHES**

- Duraplas® black thermoplastic coating

**MOUNTING OPTIONS**

- Direct surface mount to concrete walls
- Can be anchored directly into concrete masonry units
- Wood studs/ledgerboard
- Product can be mounted onto Side Stage™ and Center Stage™ systems when no appropriate backing exists, or wall mounting is not desirable

**SPACE USE RECOMMENDATIONS**

- Distance from ground to bottom of rack minimum: 47"
- Ceiling height: 82" minimum, 92" for offset installation (*shown*)
- Side wall to reference point: Minimum 18" left of reference  
 Minimum 21.5" right of the reference point
- Distance between racks center to center:  
 For racks not offset: 31" Minimum, 34" Recommended  
 For racks offset: 15.5" Minimum, 17" Recommended

For layout, ordinance or planning assistance, please contact our planning team @ 800-630-7225

